



(with optional fixed shelving and fire exit option)

Flammables Store Model FS 6.0

- Dimensions:** 2500w x 6000d x 2600h mm
- Storage:** Can be supplied without shelving or with either fixed heavy duty shelving on three walls or steel adjustable shelving- see options list.
- Bund:** 2500 litre epoxy coated bund.(exceeds EPA & PPG26 requirements). Bund integrity tested and issued with bund test certificate.
- Construction:** High strength welded tubular steel framework. Steel Bund. Insulated firewall panels. Forklift pockets and roof lifting eyes. Suitable for internal or external use.
- Fire Protection:** **90 minutes Fire protection.**
 Insulated composite Firewall panels tested to BS476 part 22.
 Test Results: Stability and Integrity: 90 minutes.
 Insulation: 90 minutes.
 Test Authority: The Loss Prevention Council (LPC) UK.
 Four hour fire rating available at extra cost.
 Test Results: Stability and Integrity: 240 minutes.
 Insulation: 90 minutes.
- Ventilation:** One Hour Rated Intumescent ventilation panels fitted at high & low level on side walls. 1-3% of surface area open for ventilation as per HS(G)51. Optional Electrical Extractor- see options list.

Finish: Corrosion resistant paint finish. Plastisol coated external walls.
Standard colours red steelwork and doors.
Goosewing grey external walls with merlin grey trim.
Internal walls white.

Access: Twin hinged fire doors with lever handles, key operated locks and door closer.
Doors can be positioned on end or side walls.



Signage: Safety/warning signage fitted as standard.
External wall mounted MSDS holder.



UK: Manchester Business Park, M22 5TG
Email: sales@safetystoragesystems.co.uk

Phone: 0870 0340754
www.safetystoragesystems.co.uk

IRL: Raheen Ind. Est. Limerick.
Email: sales@safetystorage.ie

Phone: 061 225005
www.safetystorage.ie