Bunded Fuel Tanks



Bunded, double skin, steel tanks.





10,000 litre





35,000 litre

Twin skin, heavy duty welded steel tank manufactured to OFS T200(OFTEC standard for steel storage tanks)

Manufactured to BS799-5: 2010.

Paint specification: 2 coat zinc phosphate paint system to minimum 200 microns DFT. Mid sheen. Bund capacity exceeds 110% of Tank capacity as per EPA regulations.

Fittings: Vent, Lockable Fill cap, 600mm Manway (on tanks over 10000L), Bund Inspection Hatch, 1.5 " outlet.

Capacity: Dimensions(L x W x H)

1,500 Litres(330gallons)	1250 x 1250 x 1450mm
3,000 L(660g)	2500 x 1250 x 1450mm
5,000 L(1100g)	3000 x 1500 x 1650mm
10,000 L(2200g)	3000 x 2400 x 2350mm
20,000 L(4400g)	5000 x 2400 x 2350mm
35,000 L(7700g)	6000 x 3000 x 2600mm
45,500 L(10,000g)	7100 x 3000 x 3200mm

Options:

Bund / overfill Alarm
Multi level & Overfill Alarm
Hydrostatic Contents Gauge
Oil Watchman Plus Level Gauge(1km range):
Sight Tube(Push Button, UPVC):
Ocio Electronic level Gauge
-(sends data to p.c. up to 1000m away via cable)

Safety Storage Systems

UK: Manchester Business Park, M22 5TG Phone: 0870 0340754

Email: sales@safetystoragesystems.co.uk www.safetystoragesystems.co.uk

IRL: Raheen Ind. Est. Limerick. Phone: 061 225005 Email: sales@safetystorage.ie www.safetystorage.ie