

Flammables pallet Store model FS64



- Storage Capacity:** 16 no. Pallets (1250 x 1250mm) / 64 x 200 litre Drums / 16 x IBCs.
Shelf Heights: 1300mm
- External Dimensions:** L x D x H
5850 x 3300 x 3300mm
- Bund:** 4000 litre Epoxy coated steel (3.0mm) Bund.
(exceeds 110% and 25% guidelines, ref. EPA).
Bund Tested and Certified before dispatch.
Optional Polyethylene Bund for Highly Corrosive Chemicals at extra cost.
- Construction:** Store delivered to site fully assembled.
Heavy Duty, welded tubular steel framework construction.
Profiled metal wall and roof panels.
- Fire Protection:** Insulated fire walls – FM approved. Tested to BS476 part 22.
Test Results: Stability and Integrity: 144 minutes.
Test Authority: The Loss Prevention Council (LPC) UK.
FM approval to FMRC 4880 class 1 Fire protection.
- Finish:** Corrosion resistant, 2 pack polyurethane paint finish.
Epoxy coating on Steel Bunds. PVC Plastisol finish on external walls.
Standard Colours: Red framework RAL 3020, Goosewing grey walls with merlin grey trim. Other colours possible.
- Ventilation:** Intumescent ventilation louvres on end walls at high and low level.
Vents self seal in the event of fire.
- Floors/Shelves:** Pallets stored on tubular steel Shelf Rails.
Optional removable, galvanised open mesh grating on all shelf levels.
(allows storage of non palletised goods)
- Access/Security:** Twin Sliding Doors c/w Heavy duty Pad Lock eyes.
Sliding Doors on two sides.

Signage:

Hazard / Warning Signs fitted to doors as standard.



UK: Manchester Business Park, M22 5TG
Email: sales@safetystoragesystems.co.uk

Phone: 0870 0340754
www.safetystoragesystems.co.uk

IRL: Raheen Ind. Est. Limerick.
Email: sales@safetystorage.ie

Phone: 061 225005
www.safetystorage.ie